

Futura Spas Quick Start Card


in.ye-3 North American version All 2 Pump Models

1- Remove spa access panel on the side with the touch pad control
 Remove the decorative screw covers with a small flat bladed screw driver to expose the screws. Next remove the screws and slide the side panel down below the spas lip. The panel will now be able to be bowed out slightly to release it from the tongue and groove slats

2- Connect the main power
 All two pump Futura Spas require a 50 AMP four wire GFCI protected circuit. The circuit must have two hot wires, a neutral wire and an isolated ground wire. Consult with a certified electrician or your local building inspector for wire size or additional building code requirements.

Open the in.ye-3 control box by loosening the four Phillips head screws.

Connect wiring of the electrical service box GFCI. Neutral wire is mandatory.



3- Fill Spa to approximately 8 inches from the top

4- Turn Power on to the spa. The spa will go through the following start up sequence.

Display sequence at start up (every parameter is displayed for 2 seconds)



Lamp test



Software number



Software revision



Low-level selected

After the spas diagnostic tests the system will verify water flow. Both pumps will come on at full speed for 2 to 5 minutes. During this time the display will show “- - -“. After water flow has been determined to be sufficient the secondary pump will shut down and the primary pump will switch to its low speed. The display will then revert to the time of day. Replace the control box cover and spa side.

Congratulations, your spa is now running and ready to use. Refer to the owners manual that came with the spa for programming instructions. The manual can also be found online at www.futuraspas.com/support.

